

Invented for life



**BOSCH**

# **GVC1-MX (MTS 6534)**

Vehicle communication interface for OEMs





Drawing on 30 years of experience with diagnostic environments, Bosch engineers these products in-house and produces the VCIs at one of its factories in Germany. Large volume requirements can also be met, for example for globally launching a new VCI.

#### **Workshop efficiency**

This interface sets industry benchmark for J2534 VCI pass-thru performance with its fast processor, optimized software structure, and faster boot-up. The software also facilitates reliable strategies for securely reprogramming immobilizer systems.

#### **Hardware features**

The GVCi-MX supports an extended temperature range from 20° to 70°C, sleep/wake modes, and IP54 ingress protection.

#### **Support for future vehicle architectures**

DoIP (diagnostics over IP), 4 independent CAN High speed (CAN HS) controllers let the GVCi-MX support nearly all industry-standard vehicle architectures.

#### **Extendible support for vehicle protocols**

GVCi-MX can support nearly all vehicle communication protocols, including current industry-standard protocols, OEM proprietary, and legacy protocols.

#### **Support for 24-volt systems**

The GVCi-MX VCI input voltage range is from 8 to 28 volts. The GVCi-MX supports 24-volt systems used in light and heavy trucks.



*G-VCI MX with P2P Wi-Fi: kit contents*

# GVCI-MX

## Vehicle communication interface

**4 LEDs**  
Indicate VCI status at a glance

**Placeholder**  
for optional  
customer logo

**Rubber  
end boots**  
For VCI and  
vehicle  
protection



**1 high-speed  
USB host  
connector  
(Type A)**  
Used for trigger  
interface or  
other accessory



**Power-through diagnostic  
connector or USB  
type B connector**  
Used for trigger interface  
or other accessory

**1 high-speed  
USB interface  
(Type B)**  
PC interface  
connection



## Product information

### Supported standards:

- ISO 22900-2: Diagnostic protocol data unit (D-PDU API)
- J2534-1 Version 04.04: Recommended practice for pass-thru vehicle programming
- J2534-2 Version 04.04: Pass-thru extended features

### PC host interfaces:

- USB 2.0 - type B connectors (x1)
- 802.11 b/g/n Wi-Fi

### VCI Manager (PC software):

- Device busy/wireless detection indication
- Software and firmware update tool
- Wired/wireless connection management

### VCI physical layer interfaces:

- Four CAN high speed channels
- One Ethernet channel
- Two UART channels (K and L lines)
- One J1850
- One J1708

### Protocol interfaces:

- SAE J1939 (3 independent channels)
- SAE J1708/J1587
- SAE J1850 VPW / PWM
- SAE 2740 (GM UART)
- SAE J2818 - KWP1281
- SAE J2284 at 125/250/500 kbps
- SAE J2411 (GM single-wire CAN)
- SAE J2610
- ISO 13400 - DoIP
- ISO 15765
- ISO 14230 - KWP 2K
- ISO 9141-2
- ISO 11898-1 CAN High Speed
- ISO 11898-3 (fault-tolerant CAN)
- GMW 3110 (GM LAN)
- ISO 11992-1 DW CAN

### Other available services:

- Engineering services available to assist customers with product integration
- Global network of product support centers to support the workshops

**Robert Bosch GmbH**  
Automotive Aftermarket

Franz-Oechsle-Straße 4  
73207 Plochingen  
Germany